

**LadderStow** - Fast, safe and simple ladder transportation.

The LadderStow provides an easy-to-use and ergonomic solution for loading and unloading ladders on low roof commercial vehicles - all from the convenient and safe position behind the vehicle. This eliminates the need to stretch or climb on a tyre to access the ladder, which is a considerable health and safety risk.



20 mins

**fitting time**

In addition to this, the adjustable guide post and strap help keep your ladders in place.

## DIMENSIONS

### Dimensions

- Side rail length
- Side rail height
- Width

### Weight

- Overall weight

### Capacity

- Carry capacity

(L1) 3000mm

(H1) 59mm



(W1) 569mm

### Measurements

15kg

40kg


Adjustable height and width for different ladder types and sizes




## STANDARD FITTING BRACKET

The LadderStow comes with our standard fitting bracket that is compatible with all Rhino roof bars/racks and roof storage systems from other manufacturers\*.

Every Rhino LadderStow is supplied with a set of spacers that are slotted into the bracket in a specific position to suit our AluminiumRack, ModularRack, DeltaBar and KammBar products respectively.



### Bar profile dimensions



\* The LadderStow can also be used on any other roof bar or roof rack system that fits within these dimensions.

**Note:** the system will also need to have the requisite number of cross bars.



Standard fitting bracket



LadderStow can accommodate up to 3 nested ladder sections

Rhino LadderStow  
240 CRASH TESTED



TEL: +64011244 803284

## FEATURES



**Adjustable guide post**  
Adjustable height for different ladder types



**Adjustable strap and buckle**  
Fixing ladder in place at the rear

MATERIAL	WHERE USED	ADVANTAGES
<b>Aluminium 6060 T6</b>		
- Anodised clear	- Side rails	- Extremely durable, high tensile and yield strength - Excellent weight to strength ratio - Scratch resistant
<b>Composites</b>		
- Econyl GF30%	- Moulded hand knob guide post	- Low weight, high strength ratio - High temperature variance - UV resistant
<b>Polyester</b>		
- 100% polyester, red	- Belt strap assembly	- Excellent strength - Wear resistant - UV resistant
<b>Copolymers</b>		
- Polypropylene PPCP	- Clamp cowl pacer and infill - Non lockable clamp cowl - LadderStow slider pad	- Excellent impact strength - Robust, sturdy design - UV resistant
<b>Mild steel CR4</b>		
- Powdercoated textured black	- Front retainer brackets - Webbing clamp / end bar - Rear strap beam	- High strength - Wear resistant - Corrosion protected
<b>Mild steel electroplated</b>		
- Zn8 2c Trivalent full pass. (silver)	- T track lock plate M8 - Universal clamp	- Durable - Rust free - Luxury finish
<b>Fixings</b>		
- Multi-grip pop rivets (main connection method) - Bolts & (self locking) nuts size M8, combination of stainless and galvanised steel		
<b>Tools required for installation</b> 🔧		
- Allen key (included)	- 1x spanner 10mm - 1x spanner 13mm	- Ladder

